


Texmate developed the world's first loop powered meters. We continue our leadership with the new micro processor loop powered displays with dual totalizers, square root and an optional setpoint.



SD-60XI
6 digit, 0.51" (13 mm,)
7 segment LCD display

✓ Ideal for Flow, Total Flow and Level Applications

- Front panel calibration
- Dual totalizers with setpoint reset
- Square root extraction
- One S.S.R. setpoint with 7 timer modes including hysteresis, deviation latch and reset functions.
- Smart filtering provides stable and fast response readings.
- 3.9 V loop drop (6.2 V if S.S.R. is installed)
- 1/8 DIN 96x48x13 mm (3.78"x1.89")
Ultra short depth case



SD-50X

- Front panel calibration for any required engineering units
- Simple front panel calibration
- Dip SW selectable C, F or dummy zero.
- 3.9 V loop drop

✓ Ideal for Flow, Total Flow, PSI Torque and Weighting Applications



Optional NEMA-4X Clear Lockable Water & Dust Proof cover
P/N: OP-N4X/96X48



SB-B31 Series 1/16 DIN 96x24 mm (3.78"x0.95")
Short depth meter with 31 segment LED display.

- Quick, easy mounting into any panel thickness
- Direct flush mount into mosaic panels
- Max 3.9 V loop drop.
- Available vertical or horizontal



SD-802XI

Touch-Pad Faceplate
Push Button Faceplate


- Dual totalizers for sub and grand total processing
- Three external inputs using contact closures for resetting totalizer 1 and totalizer 2
- Single 210mA, 400VDC S.S.R. setpoint with 7 timer modes. • Relay latching. • Manual relay reset.
- Programmable safety lockout to prevent tampering.
- Peak and valley retention. • Square root extraction.



DVM-5/CL

The world's smallest loop powered Process 4-20 mA LED meter.

- 1.45" x 0.59" (37 x 15 mm) CASE
- 3.5 digits, 0.276" LED display.
- Max 8 V DC loop drop.
- Factory scalable to directly read in any engineering unit.



CM-35XT

Process 4-20mA
0.48" LCD Slim bezel case

- 6.5 V loop drop
- Fully user scalable to directly read in any engineering unit
- Header programmable decimals trailing '0' digit or C and F descriptors
- Reading hold

CM-35XTL

- Less than 1 V DC loop drop.
- Optional push-on terminal connector, **CN-PUSH/CM** or PCB edge connector.



CN-L10.

- For ordering info:
Call: 1-800-TEXMATE or 760 598-9899
- Email: orders@texmate.com • 24 Hours
- For tech assistance call: (760) 598-9899