

## Texmate DV series Analog with Digital Display Switchboard Meter



**Accuracy:**  
Pointer: class 1.5  
Digital Display:  $\pm 0.5\% + 2$  counts

Alternative 3 phases Digital Indicators and Controllers. See flyer (Z667)



Switch Board Panel Cutout Adapter Plate (p/n:OP-PMA/SWBD)

Product Description	Model #	Input Range Description	Measurement Range	Power Supply	Operating Frequency
AC Amp Meter with Rectifier	DV-ACA-01 DV-ACA-05 DV-ACA-20 DV-ACA-001	1A AC 5A AC 20A AC 100mA AC	0 – 100mA, 0 – 20A External CT: specify 1A or 5A	AC/DC 85 – 260V DC 24V	50 Hz 60 Hz
AC Volt Meter with Rectifier	DV-ACV-010 DV-ACV-100 DV-ACV-110 DV-ACV-120 DV-ACV-500	10V AC 100V AC 110V AC 120V AC 500V AC	0 – 10V, 0-500V External PT: 100V, 110V, 120V AC	AC/DC 85 – 260V DC 24V	50 Hz 60 Hz
DC Amp Meter	DV-DCA-010 DV-DCA-50 DV-DCA-60 DV-DCA-75 DV-DCA-100 DV-DCA-001	10A DC 50mV DC 60mV DC 75mV DC 100mV DC 100uA DC	0 – 100uA, 0 – 10A External shunt: 50mV, 60mV, 75mV	AC/DC 85 – 260V DC 24V	50 Hz 60 Hz
DC Volt Meter	DV-DCV-050 DV-DCV-500	50mV DC 500V DC	0 – 50mV, 0 – 500V > 450V use an external resistor (Rated 5 mA)	AC/DC 85 – 260V DC 24V	50 Hz 60 Hz