


# Texmate Loop Powered Flow/Rate Meters

Texmate developed the world's first loop powered meters. We continue our leadership with the new micro processor loop powered displays with dual totalizers, square root and an optional setpoint.



Click here to shop



**SD-60XI**  
 6 digit, 0.51" (13 mm,) 7 segment LCD display  
 ✓ Ideal for Flow and Level Applications

- Front panel calibration
- Dual totalizers with external reset
- Square root extraction
- One S.S.R. setpoint with special function modes including hysteresis, deviation, latch, and reset functions.
- Smart filtering provides stable and fast response readings.
- 3.9 V loop drop (6.2 V if S.S.R. is installed)
- 1/8 DIN 96x48x13 mm (3.78"x1.89") Ultra short depth case



**SD-50X**  
 ✓ Ideal for Flow, Total Flow, PSI Torque and Weighting Applications

- Front panel calibration for any required engineering units
- Dip SW selectable C, F or dummy zero.
- 3.9 V loop drop

Optional NEMA-4X Clear Lockable Water & Dust Proof cover  
 P/N: OP-N4X/96X48



• For ordering info:  
 Call: 1-800-TEXMATE or 760 598-9899  
 Email: [orders@texmate.com](mailto:orders@texmate.com)  
 Technical Assistance: [techsupport@temate.com](mailto:techsupport@temate.com)



**SB-B31** Series 1/16 DIN 96x24 mm (3.78"x0.95") Short depth meter with 31 segment LED display.

- Quick, easy mounting into any panel thickness
- Direct flush mount into mosaic panels
- Max 3.9 V loop drop.
- Available vertical or horizontal



**SD-802XI**



- Dual totalizers with external inputs for resetting totalizer 1 and totalizer 2.
- Single 210mA, 400VDC S.S.R. setpoint with special function modes.
- Relay latching.
- Manual relay reset.
- Programmable lockout to prevent tampering.
- Peak and valley retention.
- Square root extraction.

✓ Ideal for Flow, Rate & Total Flow Applications  
 Two lines of 8 digit 7x5 dot matrix 5.5 mm positive reflective LCD displays



**MINI-CL4-20**  
 The world's smallest loop powered Process 4-20 mA LED meter.

- 1.45" x 0.59" (37 x 15 mm) case
- 3.5 digits, 0.276" 7mm LED display.
- Max 7V drop.
- Factory scalable to directly read in any engineering unit.

**SPM-083CL**

- Dimmable
- 1.77"W x 0.71"H (45x18mm) case
- 3.5 digits, 0.276" 10mm LED display.
- Crompton 083 Series Replacement



**CM-35XT**

Process 4-20mA  
 0.48" LCD Slim bezel case

- 6.5 V loop drop
- Fully user scalable to directly read in any engineering unit
- Header programmable decimals trailing '0' digit or C and F descriptors
- Reading hold
- Optional push-on terminal connector, **CN-PUSH/CM**



or PCB edge connector.

