




Click here to shop



SD-60XI

6 digit, 0.51" (13 mm,)
7 segment LCD display

✓ Ideal for Flow, Total Flow
and Level Applications

- Front panel calibration
- Dual totalizers with setpoint reset
- Square root extraction
- One S.S.R. setpoint with 7 timer modes including hysteresis, deviation latch and reset functions.
- Smart filtering provides stable and fast response readings.
- 3.9 V loop drop (6.2 V if S.S.R. is installed)
- 1/8 DIN 96x48x13 mm (3.78"x1.89")
Ultra short depth case



Texmate developed the world's first loop powered meters.
We continue our leadership with the new micro processor loop powered displays with dual totalizers, square root and an optional setpoint.



SB-B31 Series 1/16 DIN 96x24 mm (3.78"x0.95") Short depth meter with 31 segment LED display.

- Quick, easy mounting into any panel thickness
- Direct flush mount into mosaic panels
- Max 3.9 V loop drop.
- Available vertical or horizontal



SD-802XI

- Dual totalizers for sub and grand total processing
- Three external inputs using contact closures for resetting totalizer 1 and totalizer 2
- Single 210mA, 400VDC S.S.R. setpoint with 7 timer modes. • Relay latching. • Manual relay reset.
- Programmable safety lockout to prevent tampering.
- Peak and valley retention. • Square root extraction.

✓ Ideal for Flow and
Total Flow Applications
Two lines of 8 digit 7x5 dot
matrix 5.5 mm positive
reflective LCD displays

SD-50X



- Front panel calibration for any required engineering units
- Simple front panel calibration
- Dip SW selectable C, F or dummy zero.
- 3.9 V loop drop

✓ Ideal for Flow, Total Flow, PSI
Torque and Weighting Applications



Optional NEMA-4X Clear
Lockable Water & Dust
Proof cover
P/N: OP-N4X/96X48



CM-35XT

Process 4-20mA
0.48" LCD Slim bezel case

- 6.5 V loop drop
- Fully user scalable to directly read in any engineering unit
- Header programmable decimals trailing '0' digit or C and F descriptors
- Reading hold
- Optional push-on terminal connector, **CN-PUSH/CM** or PCB edge connector.



DVM-5/CL and DVM-5/DIM

The world's smallest loop powered
Process 4-20 mA LED meter.

- Dimmable
- 1.45" x 0.59" (37 x 15 mm) CASE
- 3.5 digits, 0.276" LED display.
- Max 8 V DC loop drop.
- Factory scalable to directly read in any

• For ordering info:
Call: 1-800-TEXMATE or 760 598-9899
• Email: orders@texmate.com • 24 Hours
• For tech assistance call: (760) 598-9899



CN-L10.